

Technical data

Insulation thickness		_		11/8"		27/8"		27/8"		_		1%"		11/8"		11%"	1%"	
Box height		4¾"		5½"		85%"		85%"		4½"		5½"		121/4"		7%"	5½"	
System of quick installation in the ceiling		_		_		_		_		_		_		+		+ self-assembling	+	
Step width		3%"		3%"		31/8"		3%"		3%"		3%"		5%"		3%"	3%"	
Ceiling height	Maximum (standard)	8'11"	10'1"	8'11"	10'1"	10'8"	8'11"	10'1"	8'11"	10'1"	8'11"	10'1"	8'11"	10'1"	9′21⁄4″	10′	9'21⁄4"	9'10"
	Minimum ¹	7'5"	7'10"	7'5"	7'10"	8'81/2"	7'5"	7'8"	7'2"	7'11"	7'2"	7'11"	7'2"	7'11"	7′7¾″	8'4¾"	7'6½"	7'10½"
	With additional steps LSS ²	_	_	_	_	_	_	_	_	_	_	_	_	_	_	_	9'2¼''-10'10"	9'10''-10'6''

¹ CAUTION! for rooms lower than maximum height it is necessary to adjust the ladder length according to fitting instructions

² while ordering LSS step – the ladder commercial size and type has to be provided